

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	1	(fasten\$3 and (muzzle or nosepiece) and piston and ((position\$3 or adjust\$4 or move\$3) same member) and surface and ((attach or mount or couple) same rotat\$3)).clm.	US-PGPUB; USPAT; EPO; JPO	OR	ON	2005/09/15 08:51
L2	1	("2915754").PN.	US-PGPUB; USPAT; EPO; JPO	OR	OFF	2005/09/15 08:51
L3	233	227/140.ccls.	US-PGPUB; USPAT; EPO; JPO	OR	ON	2005/09/15 08:52
L4	8	3 and wheel	US-PGPUB; USPAT; EPO; JPO	OR	ON	2005/09/15 08:52
L5	5	3 and knob	US-PGPUB; USPAT; EPO; JPO	OR	ON	2005/09/15 08:52
S1	2	((("3670941") or ("5261588"))).PN.	US-PGPUB; USPAT; EPO	OR	OFF	2005/03/24 08:38
S2	4	((("4729698") or ("4655653") or ("4572715") or ("4290464"))).PN.	US-PGPUB; USPAT; EPO; JPO	OR	OFF	2005/03/24 08:39
S3	17	("1909369" "2888680" "2915754" "3305156" "3822817" "4025031" "4346831" "5054678").PN. OR ("5261588").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2005/03/24 11:41
S4	40	("2576090" "2714905" "2733737" "2768663" "2787265" "2856799" "2982320" "2997900" "3009493" "3096798" "3107556" "3285135" "3890058" "4072440" "4349301" "4572715" "D180640").PN. OR ("4729698").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2005/03/24 11:56
S5	24	("1074800" "2797414" "2863150" "2915754" "3467294").PN. OR ("3670941").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2005/03/24 12:06
S6	26	227/130,8,110,111,151,152.ccls. and fastener and ((depth or penetrat\$4) same adjust)	US-PGPUB; USPAT; EPO; JPO	OR	ON	2005/03/24 12:07

S7	21	227/119,124,142.ccls. and fastener and ((depth or penetrat\$4) same adjust)	US-PGPUB; USPAT; EPO; JPO	OR	ON	2005/03/24 12:08
S8	32	S6 or S7	US-PGPUB; USPAT; EPO; JPO	OR	ON	2005/03/24 12:08
S9	50	herelier-p\$.in.	US-PGPUB; USPAT; EPO; JPO	OR	ON	2005/09/13 12:59
S10	50	herelier-pat\$.in.	US-PGPUB; USPAT; EPO; JPO	OR	ON	2005/09/13 13:30
S11	10	("4405072" "5197646" "5261587" "5263626" "5263842" "5320268" "5495973" "5687899").PN. OR ("6138887").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2005/09/13 13:26
S12	9	"227"/\$.ccls. and fasten\$3 and ((muzzle or nosepiece) same (depth or adjust)) and (lateral with (adjust or position))	US-PGPUB; USPAT; EPO; JPO	OR	ON	2005/09/13 13:32
S13	18	fasten\$3 and ((muzzle or nosepiece) same (depth or adjust)) and (lateral with (adjust or position))	US-PGPUB; USPAT; EPO; JPO	OR	ON	2005/09/13 13:36
S14	50083	fasten\$3 and ((spacer same substrate) or (lateral same (position or adjust)))	US-PGPUB; USPAT; EPO; JPO	OR	ON	2005/09/13 13:37
S15	239	fasten\$3 and ((spacer same substrate) or (lateral same (position or adjust))) and (muzzle or nosepiece)	US-PGPUB; USPAT; EPO; JPO	OR	ON	2005/09/13 13:38
S16	50	fasten\$3 and ((spacer same substrate) or (lateral same (position or adjust))) and (muzzle or nosepiece) and driver	US-PGPUB; USPAT; EPO; JPO	OR	ON	2005/09/13 13:38